



Stand Model  
(Vertical)



In-Line Pipe  
Mounted Model

# T Series

EPOXY COATED DIAPHRAGM TANKS

### FEATURES

**Deep Drawn Steel Shells:** provide maximum material strength.

**Inner Shell:** Prevents diaphragm from over-expanding.

**Heavy Duty Parabolic Diaphragm:** this new diaphragm design has improved diaphragm life by reducing abrasive wear. The diaphragm separates air and water to maintain the tank's air charge. The Butyl rubber diaphragm is an FDA approved material and also meets NSF / ANSI 61 - G standards.

**Interior Tank Lining:** Tank features a durable fusion bonded polymeric lining. Meets FDA requirements.

**Maximum Working Pressure:** 100 PSI.

**Temperature Rating:** Maximum 120° F.

**Epoxy Coated System Connection:** On all stand and in-line models.

**Appliance Appearance Exterior Finish:** Tan color, high durability exterior finish of tough, powder coat over a zinc phosphate surface treatment.

**Tanks are designed for installation indoors or where they are protected from rain, irrigation overspray, salt air and other corrosive environments.** Always protect tanks from freezing.

**Heavy Duty High Density Polypropylene Base:** Eliminates corrosion due to condensation and exposure to the elements.

*Tanks have a 5-year limited warranty. See instruction manual for complete warranty details.*

	Model No.	Total Volume (Gals.)	Drawdown in Gallons at System Operating Pressure Range of			Maximum Drawdown Vol. (Gals.)	Pre-Charge PSI	System Connection	Dimensions		Shipping Weight	Height From Floor to Center of Base Opening
			20/40 PSIG	30/50 PSIG	40/60 PSIG				Diameter	Height		
<b>Stand Models</b>	T45	13.9	5.1	4.3	3.7	8.4	38	1" NPTF	15 <sup>3</sup> / <sub>8</sub>	24 <sup>1</sup> / <sub>6</sub>	24	3 <sup>3</sup> / <sub>8</sub>
	T60	19.9	7.3	6.1	5.3	12.1	38	1" NPTF	15 <sup>3</sup> / <sub>8</sub>	32 <sup>3</sup> / <sub>8</sub>	34	
	T80	25.9	8.9	7.7	6.7	13.9	38	1" NPTF	15 <sup>3</sup> / <sub>8</sub>	39 <sup>1</sup> / <sub>6</sub>	43	
	T100	31.8	11.8	9.9	8.6	13.8	38	1" NPTF	15 <sup>3</sup> / <sub>8</sub>	47 <sup>1</sup> / <sub>4</sub>	52	
	T140	45.2	16.5	13.9	12.1	27.3	38	1 <sup>1</sup> / <sub>4</sub> " NPTF	22	36 <sup>3</sup> / <sub>8</sub>	64	3 <sup>3</sup> / <sub>8</sub>
	T200	65.1	23.9	20.0	17.4	39.3	38	1 <sup>1</sup> / <sub>4</sub> " NPTF	22	48 <sup>3</sup> / <sub>8</sub>	89	
	T250	83.5	30.9	25.9	22.5	50.8	38	1 <sup>1</sup> / <sub>4</sub> " NPTF	26	46	116	
	T260	84.9	31.2	26.2	22.8	44.7	38	1 <sup>1</sup> / <sub>4</sub> " NPTF	22	60 <sup>1</sup> / <sub>6</sub>	113	
T350	115.9	42.9	35.9	31.3	70.5	38	1 <sup>1</sup> / <sub>4</sub> " NPTF	26	61 <sup>1</sup> / <sub>6</sub>	161	3 <sup>1</sup> / <sub>2</sub>	
<b>In-Line ① Models</b>	T15P	4.9	1.8	1.5	1.4	3.1	38	3/4" NPTM	11	14 <sup>3</sup> / <sub>4</sub>	11	
	T25P	7.3	2.7	2.3	2.1	3.1	38	3/4" NPTM	11	21 <sup>1</sup> / <sub>6</sub>	16	
	T45P	13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 <sup>3</sup> / <sub>8</sub>	21 <sup>1</sup> / <sub>6</sub>	24	

### NOTES:

P = Pipe Connection (All dimensions are in inches and weight in lbs. Do not use for construction purposes.)

① T15P and T25P are produced at Charlotte, NC plant after January 2013, resulting in minor dimensional changes.

### ACCESSORIES



#### AW39T Bracket:


Universal pump mounting bracket for use on all tan stand model tanks.

Order No.	Description	Wt. (lbs.)
AW39T	Universal Jet Pump Bracket - Tan	2

**xylem**  
Let's Solve Water

Xylem, Inc.  
2881 East Bayard Street Ext., Suite A  
Seneca Falls, NY 13148  
Phone: (866) 325-4210  
Fax: (888) 322-5877  
www.centripro.com

CentriPro is a trademark of Xylem Inc. or one of its subsidiaries.  
© 2012 Xylem Inc. BCPT R2 January 2013

 Certified to ANSI/NSF 61